



Yapısı

Construction

- ① 1x0.22 mm² Bükülü OFC Teller / Stranded OFC Wires
- ② Ø 1.5mm Köpüklü PE / Foam PE
- ③ Yarı İletken PE Tabaka / Semi-Conduct PE Layer
- ④ Tavlı Bakır Spiral Ekranlama / Annealed Copper Spiral Screening
- ⑤ Ø 6.2mm Esnek PVC Dış Kılıf / Flexible PVC Outer Sheath

Kullanım Yerleri

Application

IC Unbalanced 22 Violine gitar, org ve ses cihazlarında kullanılan esnek, dengesiz, profesyonel enstruman kablosudur. İyi elektriksel değerleri ve yüksek mekanik dayanımı vardır.
IC Unbalanced 22 Violine is a flexible unbalanced professional instrument cable for guitar, keyboard and line level devices. It has good electrical values and high mechanical reliability.

Teknik Bilgiler

Technical Data

	IC Unbalanced 22		IC Unbalanced 22
İletken Direnci Conductor Resistance	<85 Ω/km	Yayıma Hızı Velocity of Propagation	-
Ekran Direnci Screen Resistance	<55 Ω/km	Test Voltajı Test Voltage	2.5 kV
Zayıflamalar Attenuations	-	Çalışma Voltajı Working Voltage	1.1 kV
Kapasite Capacity	<115 nF/km	Yalıtım Direnci Insulation Resistance	> 3.2 G.Ω.km
Empedans Empedance	-	Çalışma Sıcaklığı Working Temperature	-30°C... +70°C